


NP4-4.5Ah 4V4.5Ah




Specifications

Nominal Voltage		4V
Rated capacity (20 hour rate)		4.5Ah
Dimensions	Length	47±1mm(1.85inch)
	Width	47±1mm(1.85inch)
	Height	101±1mm(3.98inch)
	Total Height	107±1mm(4.21inch)
Approx. Weight		0.52kg(1.15lbs)±5%

Outer dimensions (mm)



Terminal Type (mm)



Characteristics

Capacity (25°C)	20HR(3.50V)	4.5Ah
	10HR(3.50V)	4.2Ah
	1HR(3.20V)	2.7Ah
Terminal type		T1
Internal resistance (Fully charged,25°C)		Approx. 15m Ω
Capacity affected by temperature (20HR)	40°C	102%
	25°C	100%
	0°C	85%
	-15°C	65%
Self-discharge (25°C)	3 months	Remaining Capacity:91%
	6 months	Remaining Capacity:82%
	12 months	Remaining Capacity:65%
Nominal operating temperature		25°C ±3°C(77°F ±5°F)
Operating temperature range	Discharge	-15°C~50°C(5°F~122°F)
	Charge	-10°C~50°C(14°F~122°F)
	Storage	-20°C~50°C(-4°F~122°F)
Float charging voltage(25°C)		4.50 to 4.60V Temperature compensation: -6mV/°C
Cyclic charging voltage(25°C)		4.80 to 5.00V Temperature compensation: -10mV/°C
Maximum charging current		1.35A
Maximum discharge current		68A(5 sec.)
Designed floating life(20°C)		5 years

Construction

Component	Positive plate	Negative plate	Container	Cover	Separator	Electrolyte	Safety valve	Terminal
Raw material	Lead dioxide	Lead	ABS	ABS	AGM	Sulfuric acid	Rubber	Copper

Constant Current Discharge Characteristics Unit:A(25°C,77°F)

F.V/Time	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
3.20V	17.2	10.9	8.51	4.79	2.95	1.61	1.12	0.92	0.78	0.43	0.23
3.30V	16.7	10.6	8.30	4.70	2.90	1.60	1.11	0.92	0.78	0.42	0.23
3.40V	16.0	10.1	7.99	4.55	2.83	1.59	1.10	0.91	0.77	0.42	0.23
3.50V	15.3	9.69	7.72	4.44	2.77	1.56	1.09	0.90	0.77	0.42	0.23
3.60V	14.4	9.15	7.31	4.28	2.69	1.52	1.06	0.88	0.75	0.41	0.22


Constant Power Discharge Characteristics Unit:W(25°C,77°F)

F.V/Time	5min	10min	15min	30min	60min	2h	3h	4h	5h	10h	20h
3.20V	63.9	40.9	32.3	18.3	11.4	6.29	4.42	3.66	3.12	1.70	0.91
3.30V	62.0	39.7	31.5	17.9	11.2	6.25	4.39	3.64	3.11	1.70	0.91
3.40V	59.5	38.1	30.4	17.4	10.9	6.20	4.36	3.62	3.08	1.69	0.91
3.50V	56.9	36.4	29.3	17.0	10.7	6.10	4.33	3.59	3.06	1.68	0.90
3.60V	53.7	34.4	27.8	16.3	10.4	5.95	4.20	3.48	2.97	1.65	0.88


Note: The above characteristics data can be obtained within three charge or discharge cycles.

NP4-4.5Ah 4V4.5Ah


● **Discharge characteristics(25°C)**




● **Charging characteristics (25°C)**




● **Effect of temperature on capacity**




● **Self-discharge characteristics**




● **Floating life on temperature**



● **Cycle life on D.O.D(25°C)**



● **The relationship for OCV and Capacity (25°C)**



● **The relationship for Charging voltage and Temperature**

